


tML® - FO Patch Cord Management 19" Panel 1U, 5 rings 56mm, stainless steel



tML® 24

tML® 24 is a patented, modular cabling system consisting of the three key components module, trunk cable and rack mount enclosure. The system components are 100 percent manufactured, pre-assembled and tested in Germany. They enable plug-and-play installation on site – especially in data centres, but also in industrial environments – within the shortest possible time. Heart of the system are the rear MPO/MTP® 24 fiber and Telco connectors, which can be used to connect at least six or twelve ports at a time. Depending on the module configuration, transfer rates of up to 400G are currently possible with SR4. The fibre optic and TP modules can be used together in a module carrier with a very high port density. The tde offers its tML® cabling system as a proven tML® standard system and in the highly innovative variants tML®Xtended and now tML® 32 for extreme scalability and very easy migration to higher transmission rates such as 40G, 100G, 200G and 400G.

tML® - FO Patch Cord Management 19" Panel for the regulatory horizontal cable run of patch cords.



tde® trans data elektronik GmbH

Headquarter address:

Lingener Str. 2
D-49626 Bippen/Ohrte
Tel.: +49 5435 9511 0
Fax.: +49 5435 9511 32

Sales office address:

Prinz-Friedrich-Karl-Str. 46
D-44135 Dortmund
Tel.: +49 231 8805 61 13
Fax.: +49 231 8805 61 15

info@tde.de | www.tde.de

tML® - FO Patch Cord Management 19" Panel 1U, 5 rings 56mm, stainless steel

Technical Data

Front plate	stainless steel
Assembly	5 rings 56mm
Cable entry	Patch cords are from the front inserted
Size	19", 1U
	QS-Managementsystem ISO 9001, ISO 14001 and TL 9000

Product variants & accessories

Art.-No.	Description
TML-RP-L-5	tML® - FO Patch Cord Management 19" Panel 1U, 5 rings 56mm, stainless steel
TML-RP-L-5-S	tML® - FO Patch Cord Management 19" Panel 1U, 5 rings 56mm, black