



tML® - TP Patch Cord Managment 19" Panel 1U, 5 rings 75mm, stainless steel



### tML® - tde Modular Link

tML® is a patented, modular cabling system consisting of the three key components module, trunk cable and rack mount enclosure. The system components are 100 percent manufactured, pre-assembled and tested in Germany. They enable plug-and-play installation on site – especially in data centres, but also in industrial environments – within the shortest possible time. Heart of the system are the rear MPO/MTP® and Telco connectors, which can be used to connect at least six or twelve ports at a time. Depending on the module configuration, transfer rates of up to 200G are currently possible with SR4. The fibre optic and TP modules can be used together in a module carrier with a very high port density. The tde offers its tML® cabling system as a proven tML® standard system and in the highly innovative variants tML® Xtended, tML® 24 System and now tML® 32 System for extreme scalability and very easy migration to higher transmission rates such as 40G, 100G, 200G and 400G.

 $tML\mbox{\ensuremath{@}}$  - TP Patch Cord Management 19" Panel for the regulatory horizontal cable run of patch cords.



tde® trans data elektronik GmbH

### **Headquarter address:**

Lingener Str. 2 D-49626 Bippen/Ohrte Tel.: +49 5435 9511 0

Fax.: +49 5435 9511 32

#### Sales office address:

Prinz-Friedrich-Karl-Str. 46 D-44135 Dortmund

Tel.: +49 231 8805 61 13 Fax.: +49 231 8805 61 15

info@tde.de | www.tde.de



net. work. solution. made in Germany

tML® - TP Patch Cord Managment 19" Panel 1U, 5 rings 75mm, stainless steel

# **Technical Data**

Front plate	stainless steel
Assembly	5 rings 75mm
Cable entry	Patch cords are from the top inserted
Size	19", 1U
	QS-Managementsystem ISO 9001, ISO 14001 and TL 9000

# **Product variants & accessories**

ArtNo.	Description
TML-RP-TP-5	tML® - TP Patch Cord Managment 19" Panel 1U, 5 rings 75mm, stainless steel
TML-RP-TP-5-S	tML® - TP Patch Cord Managment 19" Panel 1U, 5 rings 75mm, black