

tBL® - DIN Rail Housing for 1x RJ45 Keystone Module



### tBL® - tde Basic Link (TP)

tBL® tde Basic Link (TP) is a complete system solution for structured cabling in Cat6A for transfer rates of up to 10GbE in real time. The tBL® - cabling link corresponds to a permanent link in accordance with ISO / IEC 11801 (EN 50173). The RJ45 modules are available in the form factors Keystone (KS) and Data Center (DC). The compact design of the 6fold RJ45 DC module allows a high packing density of up to 48 RJ45 ports on 1U. The RJ45 module is connected to the tBL® - cable termination block by simply plugging. The slim cable termination block can be easily assembled on the cable by using the tBL® - crimp tool and is suitable for preterminated cables. The modular design of individual RJ45 modules are interchangeable at any time without termination. A cost effective alternative product is the RJ45 keystone module without cable termination block in the tool-less design.

The system solution is complemented by an extensive portfolio of carrier systems. These include design-capable data outlets, floor box frames, Consolidation points, DIN rail modules and patch panels in 1/2 and 1U.

 $tBL^{\scriptsize @}$  - DIN rail Housing is for the attachment of one  $tBL^{\tiny @}$  - RJ45 Keystone conceives.



#### tde® trans data elektronik GmbH

### **Headquarter address:**

Lingener Str. 2 D-49626 Bippen/Ohrte Tel.: +49 5435 9511 0 Fax.: +49 5435 9511 32

# Sales office address:

Prinz-Friedrich-Karl-Str. 46 D-44135 Dortmund

Tel.: +49 231 8805 61 13 Fax.: +49 231 8805 61 15

info@tde.de | www.tde.de



net. work. solution. made in Germany

tBL® - DIN Rail Housing for 1x RJ45 Keystone Module

## **Technical Data**

Material	plastic
Color	grey, RAL 7035
Mounting	on DIN Rail by simple snap-in
	QS-Managementsystem ISO 9001, ISO 14001 and TL 9000

## **Product variants & accessories**

ArtNo.	Description
TBL-HU-RJ45KS-W/O	tBL® - DIN Rail Housing for 1x RJ45 Keystone Module
TBL-RJ45KS-TL	tBL® - RJ45 Keystone Module Cat.6 <sub>A</sub> ISO/IEC tool-less, AWG 22-24