

tde - FO Fiberpigtail E2000 50/125 μ OM2 Length: 2m



tde - Fiber Optic Assemblies

The tde patch and trunk cables are manufactured completely at the German facility in Ohrte. Production processes at tde meet the latest standards, and the company has one of the most up-to-date fiber optic assembly houses in Europe. Fiber optic patch cables and trunk cables are manufactured in many different configurations using highly automated processes on two independent mass production lines. The range of products on offer encompasses the entire spectrum of connector types available on the market. Production capacity is around 100,000 fiber optic connectors per month, and this can be ramped up easily whenever required. To guarantee consistently top quality, only the best components from renowned vendors are used. All tde production staff have the necessary qualifications and education, and have been well trained in using specialist technical equipment such as laser cleavers and glue-dispensing robots.

Each cable application is subjected to a full test procedure comprising interferometer measurements, insertion loss and return loss measurements and a final visual inspection to ensure that only 100% error-free products are shipped to the customer.

Products made by tde perform at least internationally accepted quality standards and norms. The quality management system is ISO 9001, ISO 14001 and TL9000 certified.



tde[®] trans data elektronik GmbH

Headquarter address:

Lingener Str. 2
D-49626 Bippen/Ohrte
Tel.: +49 5435 9511 0
Fax.: +49 5435 9511 32

Sales office address:

Prinz-Friedrich-Karl-Str. 46
D-44135 Dortmund
Tel.: +49 231 914 36 99
Fax.: +49 231 914 31 29

info@tde.de | www.tde.de

tde - FO Fiberpigtail E2000 50/125μ OM2 Length: 2m

Technical Data

FO Connectors

| | |
|------------------|---------|
| Type | E2000 |
| Ferrule | Ceramic |
| Ferrule Hole | 126 μ |
| Connector colour | Beige |
| Lever colour | Black |
| Boot colour | Black |
| Manufacturer | RDM |

Optical performance

| Fiber | Type | Wavelength | Insertion loss typ. | Insertion loss max. | Return loss min. |
|---------------|-------|------------|---------------------|---------------------|------------------|
| 50/125μ OM2 | E2000 | 850 nm | ≤ 0.25 dB | 0.45 dB | 30 dB |
| 62.5/125μ OM1 | E2000 | 850 nm | ≤ 0.25 dB | 0.45 dB | |

FO Cables

| | |
|--------------|--|
| Tight Buffer | Low smoke (IEC 61034 and EN 50268) and free of halogens (LSOH) |
| | Non corrosive after IEC 60754-2 and EN 50267 |
| | Flame resistant after IEC 60332-3C and EN 50266-2-4 |
| | Completely dry design |
| | Free from metal, no grounding problems and potential differences |
| | Tight Buffer for simple and direct connector mounting |

Characteristics

| | |
|--|------------------|
| Fiber Count | 1 (Tight Buffer) |
| Core-Ø | 0.9 mm |
| Coreweight | 1 kg/km |
| Min. Bending radius - Installation | 30 mm |
| Min. Bending radius - Operation | 30 mm |
| Removal | 1500 mm |
| Fire load | 0.15 MJ/m |
| Temperature range - Installation | -5 to +50°C |
| Temperature range - Operation | -20 to +60°C |
| Temperature range - Transport / Lagerung | -25 to +70°C |

FO Fiber

| | |
|--------------|-------------------------------------|
| Type | Corning 50/125μ OM2 multimode fiber |
| Manufacturer | Corning |

tde - FO Fiberpigtail E2000 50/125 μ OM2 Length: 2m

Optical Specifications

| | |
|--------------------|---|
| Bandwidth | 500 at 850 nm / 500 at 1300 nm |
| Attenuation | At 850 nm max. \leq 2.5 dB/km At 1300 nm max. \leq 0.8 dB/km |
| Numerical Aperture | 0.200 \pm 0.015 |

Dimensional Specifications

| | |
|--------------------------------|-------------------------|
| Core Diameter | 50.0 \pm 3.0 μ m |
| Cladding Diameter | 125.0 \pm 2.0 μ m |
| Core-Clad Concentricity | \leq 3.0 μ m |
| Cladding Non-Circularity | $<$ 2.0% |
| Core Non-Circularity | \leq 5.0% |
| Coating Diameter | 245 \pm 5 μ m |
| Coating-Cladding Concentricity | $<$ 12 μ m |

Environmental Specifications

| Environmental Test | Test Condition | Induced Attenuation 850 nm and 1300 nm (dB/km) |
|------------------------------|---------------------------------|--|
| Temperature Dependence | -60°C to +85°C | \leq 0.20 |
| Temperature Humidity Cycling | -10°C to +85°C and 4% to 98% RH | \leq 0.20 |
| Operating Temperature Range | -60°C to +85°C | |

Mechanical Specifications

| | |
|------------|--|
| Proof Test | The entire fiber length is subjected to a tensile stress \geq 100 kpsi (0.7 GN/m ²). |
| Length | Fiber lengths available up to 8.8 km/spool. |

Performance Characterizations

| | |
|-------------------------------------|--|
| Refractive Index Difference | 2% |
| Effective Group Index of Refraction | 850 nm: 1.490 1300 nm: 1.486 |
| Fatigue Resistance Parameter (nd) | 20 |
| Coating Strip Force | Dry: 0.6 lbs (2.7N) Wet: 14 days in 23°C water soak: 0.6 lbs (2.7N) |
| Chromatic Dispersion | Zero Dispersion Wavelength (λ_0): 1300 nm \leq λ_0 \leq 1320 nm Zero Dispersion Slope (S0): \leq 0.101 ps/(nm ² *km) |

Product variants & accessories

| Art.-No. | Description |
|----------------|---|
| L-E2/-09F00200 | tde - FO Fiberpigtail E2000 PC 9/125 μ OS2 Length: 2m |
| L-E2/-50F00200 | tde - FO Fiberpigtail E2000 50/125 μ OM2 Length: 2m |

tde - FO Fiberpigtail E2000 50/125 μ OM2 Length: 2m

| Art.-No. | Description |
|------------------|--|
| L-E2/-50F3-00200 | tde - FO Fiberpigtail E2000 50/125 μ OM3 Length: 2m |
| L-E2/-50F4-00200 | tde - FO Fiberpigtail E2000 50/125 μ OM4 Length: 2m |
| L-E2/-62F00200 | tde - FO Fiberpigtail E2000 62,5/125 μ OM1 Length: 2m |
| L-E2A/-09F00200 | tde - FO Fiberpigtail E2000 APC 9/125 μ OS2 Length: 2m |