



EOL - Finisar - SFP+ 8G Transceiver, Multimode LC, 8.5 Gb/s, 50m/150m



### **Finisar - Transceiver**

Finisar's broad product selection and innovative technology have made Finisar the optical module manufacturer of choice for all major networking equipment vendors worldwide. The products are fully compliant with Ethernet, Fiber Channel, Infiniband, SONET/SDH/OTN and PON standards and operate at data rates up to 100 Gb/s. They are capable of distances ranging from very short reach within a datacenter to campus, access, metro, and long-haul reaches. They feature outstanding performance over extended voltage and temperature ranges, while minimizing jitter, electromagnetic interference (EMI) and power dissipation.

Finisar's FTLF8528P3BNV SFP+ transceivers are designed for use in Fiber Channel links up to 8.5 Gb/s data rate over multimode fiber. They are compliant with FC-PI-4 Rev. 8.00 and SFF-8472 Rev. 11.0, and compatible with SFF-8432b, and applicable portions of SFF-8431 Rev. 4.1. The product is RoHS compliant and lead-free per Directive 2002/95/ECe and Finisar Application Note AN-2038.



tde® trans data elektronik GmbH

### **Headquarter address:**

Lingener Str. 2 D-49626 Bippen/Ohrte Tel.: +49 5435 9511 0 Fax.: +49 5435 9511 32

#### Sales office address:

Prinz-Friedrich-Karl-Str. 46 D-44135 Dortmund

Tel.: +49 231 8805 61 13 Fax.: +49 231 8805 61 15

info@tde.de | www.tde.de



net. work. solution. made in Germany

EOL - Finisar - SFP+ 8G Transceiver, Multimode LC, 8.5 Gb/s, 50m/150m

## **Technical Data**

| Key Features | Up to 8.5 Gb/s bi-directional data links            |
|--------------|---|
|              | Hot-pluggable SFP footprint                         |
|              | Built-in digital diagnostic functions               |
|              | 850 nm Oxide VCSEL transmitter                      |
|              | Duplex LC connector                                 |
|              | RoHS compliant and Lead Free                        |
|              | 50m on 50/125 μm MMF                                |
|              | 150m on high-bandwidth 50/125um (OM3) MMF           |
|              | Metal enclosure, for lower EMI                      |
|              | Single 3.3 V power supply                           |
|              | < 0.5W power dissipation                            |
|              | Extended operating temperature range: -5°C to +85°C |

| Applications | Tri-Rate 2.125/4.25/8.5 Gb/s Fiber Channel |
|--------------|--|
|              | Wireless - CPRI                            |
|              | Wireless - OBSAI                           |

| On request also available for | Brocade - XBR-000147       |
|-------------------------------|----------------------------|
|                               | Qlogic NIC - FTLF8528P3BNV |

| Weblink | http://www.finisar.com/products/optical-transceivers/sfp-plus/FTLF8528P3BNV |
|---------|---|
|---------|---|

# **Product variants & accessories**

| ArtNo.        | Description   |
|---------------|---|
| FTLF1428P2BNV | EOL - Finisar - SFP+ 8G Transceiver, Singlemode LC, 8.5 Gb/s, 10km    |
| FTLF8528P3BCV | Finisar - SFP+ 8G Transceiver, Multimode LC, 8.5 Gb/s, 50m/150m       |
| FTLF8528P3BNV | EOL - Finisar - SFP+ 8G Transceiver, Multimode LC, 8.5 Gb/s, 50m/150m |