Point System™ Adapter for the ION chassis, includes bracket and 4 screws





Direct Attach Cables / Active Optical Cables

A simple to install, cost-effective and interoperable solution

Often used for data center short-reach interconnects, Direct Attach, Active Copper and Active Optical Cables are an indispensable part of any network.

Terminated with transceiver-style connectors, they are designed to be used in the same ports as a typical SFP+ or QSFP transceiver, with no need for adapters or converters. Our DAC and AOC cables offer compatibility with a huge range of vendors, enabling the connectivity you need within the Top of Rack and End of Row environments.

- 10G, 25G, 40G & 100G product solutions
- Seamless interoperability with network equipment
- Multi-code options enabling different OEM vendors at each end of the cable
- 4x breakout cables, 40G QSFP+ to 4x 10G SFP and 100G QSFP28 to 4x 25G SFP28
- Fast Delivery, Custom solutions
- Compatible with Over 90 Systems
- Savings of up to 70%

tde® trans data elektronik GmbH

Headquarter address:
Lingener Str. 2
D-49626 Bippen/Ohrte
Tel.: +49 5435 9511 0
Fax.: +49 5435 9511 32

Sales office address:
Prinz-Friedrich-Karl-Str. 46
D-44135 Dortmund
Tel.: +49 231 8805 61 13
Fax.: +49 231 8805 61 15

info@tde.de | www.tde.de

 © tde GmbH, all rights reserved, errors excepted.

Point System™ Adapter for the ION chassis, includes bracket and 4 screws

The IONADP is an adapter card that allows the ION Platform chassis to be backwards compatible with Point System™ modules. This adapter is designed to sit between a Point System™ module and the backplane of the ION chassis. The purpose of the IONADP is to lengthen the Point System™ module so it can be securely mounted in an ION chassis while also connecting to the backplane allowing the ION chassis to power the Point System™ module.

SNMP management of the Point System™ modules installed in the ION chassis is possible by using an existing Point System™ management module along with IONADP. The ION modules and the Point System™ modules are managed independently by their own respective management modules. The ION management module and the Point System™ management module would each require a unique IP address assigned to them, while Focal Point can be used to access the management information from each management module simultaneously.

Features

- Ease the installation of legacy Point System™ cards in the ION chassis
- Redeploy Point System™ cards you own in a new ION chassis
- Lengthens a Point System™ card to match the size of the ION card
- Can be used with any Point System™ card
- Manage Point System™ cards in the ION chassis, if you have a Point System™ Management Module
- IONADP kit includes adapter card, bracket, and four screws

Technical Data

Dimensions

- Width: 0.5” [12.7 mm]
- Depth: 1.25” [31.75 mm]
- Height: 2.9” [73.66 mm]

Environment

- Environment specs are dependent on the chassis chosen
- Operating: 0°C to 50°C
- Storage: -40°C to +85°C
- Humidity: 5% to 95% (non-condensing)
- Altitude: 0 – 10,000 ft.

Weight

© tde GmbH, all rights reserved, errors excepted.

- 0.5 lbs. [0.22 kg]

Warranty

- Lifetime

Product variants & accessories

Art.-No.	Description
IONADP	Point System™ Adapter for the ION chassis, includes bracket and 4 screws

 © tde GmbH, all rights reserved, errors excepted.