

tML<sup>®</sup> Xtended - FO Dark Fiber Module 5HP black 4x MPO/MTP<sup>®</sup> w/o Pins/6x MPO/MTP<sup>®</sup> w. Pins  
50/125 $\mu$  OM5, SR4

## tML<sup>®</sup> Xtended

tML<sup>®</sup> Xtended is a patented, modular cabling system consisting of the three key components module, trunk cable and rack mount enclosure. The system components are 100 percent manufactured, pre-assembled and tested in Germany. They enable plug-and-play installation on site – especially in data centres, but also in industrial environments – within the shortest possible time. Heart of the system are the rear MPO/MTP<sup>®</sup> 12 fiber and Telco connectors, which can be used to connect at least six or twelve ports at a time. Depending on the module configuration, transfer rates of up to 200G are currently possible with SR4. The fibre optic and TP modules can be used together in a module carrier with a very high port density. The tde offers its tML<sup>®</sup> cabling system as a proven tML<sup>®</sup> standard system and in the highly innovative variants tML<sup>®</sup> 24 system and now tML<sup>®</sup> 32 system for extreme scalability and very easy migration to higher transmission rates such as 40G, 100G, 200G and 400G.



### **tde<sup>®</sup>** trans data elektronik GmbH

#### **Headquarter address:**

Lingener Str. 2  
D-49626 Bippen/Ohrte  
Tel.: +49 5435 9511 0  
Fax.: +49 5435 9511 32

#### **Sales office address:**

Prinz-Friedrich-Karl-Str. 46  
D-44135 Dortmund  
Tel.: +49 231 914 36 99  
Fax.: +49 231 914 31 29

info@tde.de | www.tde.de

tML<sup>®</sup> Xtended - FO Dark Fiber Module 5HP black 4x MPO/MTP<sup>®</sup> w/o Pins/6x MPO/MTP<sup>®</sup> w. Pins  
50/125 $\mu$  OM5, SR4

## Technical Data

The end faces of the connectors are optimized by means of Lasercleaving and machine polish. The MPO/MTP<sup>®</sup> plug has a defined fiber height of 1 - 3.5 $\mu$ . The max. adjacent fiber height difference is 0.2 $\mu$ m and for all fibers 0.3 $\mu$ m. All system components (modules, trunk cables and patch cords) are co-ordinated for the reaching of the performance particularly. The module is marked with sequential serial number and article number. The modules are ROHS compliant.

Entry	2 x MPO/MTP <sup>®</sup> Female Adapter (limegreen) back
Exit	6 x MPO/MTP <sup>®</sup> Male Adapter (limegreen) front
Tests	Interferometer, Insertion Loss, Return Loss and Visual Final Inspection; all measured values are electronically archived
	QS-Managementsystem ISO 9001, ISO 14001 and TL 9000

Box	Galvanized steel sheet
Front Panel	black

## FO Connectors

The end faces of the connectors are optimized by means of Lasercleaving and machine polish. The MPO/MTP<sup>®</sup> plug has a defined fiber height of 1 - 3.5 $\mu$ . The max. adjacent fiber height difference is 0.2 $\mu$ m and for all fibers 0.3 $\mu$ m.

### Connector

Type	MPO/MTP <sup>®</sup> Female Push Pull Locking
Ferrule	12 Fiber MM Elite <sup>®</sup> ferrule, PPS
Boot colour	Black
Manufacturer	tde/US Conec

### Optical Performance

Fiber	Type	Wavelength	Insertion loss typ.	Insertion loss max.	Return loss min.
50/125 $\mu$ OM5	MPO/MTP <sup>®</sup>	850 nm	$\leq$ 0.16 dB	0.30 dB	30 dB

## FO Connectors

The end faces of the connectors are optimized by means of Lasercleaving and machine polish. The MPO/MTP<sup>®</sup> plug has a defined fiber height of 1 - 3.5 $\mu$ . The max. adjacent fiber height difference is 0.2 $\mu$ m and for all fibers 0.3 $\mu$ m.

### Connector

Type	MPO/MTP <sup>®</sup> Male Push Pull Locking with Elite Pins
------	---

tML<sup>®</sup> Xtended - FO Dark Fiber Module 5HP black 4x MPO/MTP<sup>®</sup> w/o Pins/6x MPO/MTP<sup>®</sup> w. Pins  
50/125 $\mu$  OM5, SR4

Ferrule	12 Fiber MM Elite <sup>®</sup> ferrule, PPS
Boot colour	Black
Manufacturer	tde/US Conec

## Optical Performance

Fiber	Type	Wavelength	Insertion loss typ.	Insertion loss max.	Return loss min.
50/125 $\mu$ OM5	MPO/MTP <sup>®</sup>	850 nm	$\leq$ 0.16 dB	0.30 dB	30 dB

## FO Adapters

Type	MPO/MTP <sup>®</sup>
Application	Multimode OM5
Design	without Flange
Connector style	SC Simplex
Key Orientation	Type A, Key up/down
Color	Limegreen
Material	Plastic
Sleeve	--
Shutter	--
Standards	IEC 61754-7 TIA 604-5
Manufacturer	US Conec

## FO Fiber

Type	Corning ClearCurve <sup>®</sup> 50/125 $\mu$ OM5 multimode fiber
Design	Optical fibre G50/125 $\mu$ m (conform to IEC 60793-2-10 type A1a.4b) with optical core 50 $\mu$ m +/- 2.5 $\mu$ m diameter and optical cladding 125 $\mu$ m +/- 1 $\mu$ m diameter

## Geometrical properties

Core concentricity error	< 5 %
Coating concentricity error	< 1 %
Core coating eccentricity	< 1.5 $\mu$ m
Eccentricity of coating	< 12 $\mu$ m
Screen test	$\geq$ 0.7 GPa (100 kpsi)

## Transmission characteristics

Attenuation, maximum values 850 nm (cabled fibre)	2.5 dB/km
---	-----------

tML<sup>®</sup> Xtended - FO Dark Fiber Module 5HP black 4x MPO/MTP<sup>®</sup> w/o Pins/6x MPO/MTP<sup>®</sup> w. Pins  
50/125 $\mu$  OM5, SR4

Attenuation, maximum values 953 nm (cabled fibre)	1.8 dB/km
Attenuation, maximum values 1300 nm (cabled fibre)	0.7 dB/km
Attenuation, maximum values 850 nm (uncabled fibre)	2.34 dB/km
Attenuation, maximum values 953 nm (uncabled fibre)	1.7 dB/km
Attenuation, maximum values 1300 nm (uncabled fibre)	0.64 dB/km
Macrobending, induced attenuation 100 turns, 37.5 mm	$\leq 0.5$ dB (at 850 nm)
Macrobending, induced attenuation 100 turns, 37.5 mm	$\leq 0.5$ dB (at 1300 nm)
Macrobending, induced attenuation 2 turns, 15 mm	$\leq 0.1$ dB (at 850 nm)
Macrobending, induced attenuation 2 turns, 15 mm	$\leq 0.3$ dB (at 1300 nm)
Macrobending, induced attenuation 2 turns, 7.5 mm	$\leq 0.3$ dB (at 850 nm)
Macrobending, induced attenuation 2 turns, 7.5 mm	$\leq 0.5$ dB (at 1300 nm)
Bandwidth (OFL), minimum values 850 nm	3500 MHz x km
Bandwidth (OFL), minimum values 953 nm	1850 MHz x km
Bandwidth (OFL), minimum values 1300 nm	500 MHz x km
Effective modal Bandwidth-length product min. 850 nm	4700 MHz x km
Effective modal Bandwidth-length product min. 953 nm	2470 MHz x km
Numerical aperture	0.200 +/- 0.015
Effective group of refraction 850 nm	1.482
Effective group of refraction 1300 nm	1.477

## Product variants & accessories

Art.-No.	Description
TML-T06MPP/4MP50G3XS	tML <sup>®</sup> Xtended - FO Dark Fiber Module 5HP black 4x MPO/MTP <sup>®</sup> w/o Pins/6x MPO/MTP <sup>®</sup> w. Pins 50/125 $\mu$ OM3, SR4
TML-T06MPP/4MP50G4XS	tML <sup>®</sup> Xtended - FO Dark Fiber Module 5HP black 4x MPO/MTP <sup>®</sup> w/o Pins/6x MPO/MTP <sup>®</sup> w. Pins 50/125 $\mu$ OM4, SR4
TML-T06MPP/4MP50G5XS	tML <sup>®</sup> Xtended - FO Dark Fiber Module 5HP black 4x MPO/MTP <sup>®</sup> w/o Pins/6x MPO/MTP <sup>®</sup> w. Pins 50/125 $\mu$ OM5, SR4